



# EPOAIS 10 ELASTOMERICO, TWO COMPONENT ADHESIVE EPOXY RESIN BASED AND ELASTOMERIC



## Descripción

High performance adhesive, two-component epoxy resins. Epoais 10 is ideal for bonding fresh concrete with curing concrete. Supports incorporating ARCUAIS.

## Aplicación

- Asegura la continuidad de piezas de hormigón fraguado con hormigón fresco ( puentes, carreteras, estructuras, etc.)
- En el anclaje de hierros, relleno de grietas, etc, siempre que el taladro sea vertical o sea posible disponer de molde.
- En la unión de prefabricados de hormigón, que requieren altas sollicitaciones, relleno de fisuras sin movimiento, etc.
- En la reparación de grietas y fisuras, etc.

## Surface preparation

- Ensures continuity of hardened concrete pieces with fresh concrete (bridges, roads, structures, etc.).
- The anchoring irons, filling cracks, etc. The drill must be either vertical or there is possibility to arrange the mold
- At the junction of precast concrete requiring high stresses, filling cracks without movement, etc..
- In the repair of cracks and fissures, etc.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
Telf.: 981 602 111  
Fax.: 981 601 508  
Email: desarrollo@teais.es

síguenos en:



## Modes of application

---

## Clean up

---

With our EPOXY SOLVENT before the product hardens, once hardened, by mechanical means.

## Data sheet

---

Density

Density

Adherence

Compressive resistance

Flexural strength resistance

Temperature of work

Open time

Colour/s

## Performance

---

2 m2 per kg in concrete union

## Storage

---

1 years in original containers, tightly closed, without exposing to extreme temperatures, protected from the weather, in a dry and airy.

