



EPOAIS 10 ELASTOMERICO, TWO COMPONENT ADHESIVE EPOXY RESIN BASED AND ELASTOMERIC



Description

High performance adhesive, two-component epoxy resins. Epoais 10 is ideal for bonding fresh concrete with curing concrete. Supports incorporating ARCUAIS.

Application

- Asegura la continuidad de piezas de hormigón fraguado con hormigón fresco (puentes, carreteras, estructuras, etc.)
- En el anclaje de hierros, relleno de grietas, etc, siempre que el taladro sea vertical o sea posible disponer de molde.
- En la unión de prefabricados de hormigón, que requieren altas solicitudes, relleno de fisuras sin movimiento, etc.
- En la reparación de grietas y fisuras, etc.

Surface preparation

- Ensures continuity of hardened concrete pieces with fresh concrete (bridges, roads, structures, etc.).
- The anchoring irons, filling cracks, etc. The drill must be either vertical or there is possibility to arrange the mold
- At the junction of precast concrete requiring high stresses, filling cracks without movement, etc..
- In the repair of cracks and fissures, etc.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email: desarrollo@teais.es

síguenos en:



Modes of application

Clean up

With our EPOXY SOLVENT before the product hardens, once hardened, by mechanical means.

Data sheet

Density

Density

Adherence

Compressive resistance

Flexural strength resistance

Temperature of work

Open time

Colour/s

Performance

2 m² per kg in concrete union

Storage

1 years in original containers, tightly closed, without exposing to extreme temperatures, protected from the weather, in a dry and airy.



Avda. da Enerxía, nº 153, PoL Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email.: desarrollo@teais.es

síguenos en:

