



# UNIRRES-NC UNIVERSAL, UNIVERSAL ADHERENCE IMPROVER AGENT WHICH DOESN'T PRODUCE CORROSION ON METALS



## Descripción

UNIRRES-NC is a bonding agent to apply on metallic, wooden surfaces and with mortars, paints, etc. Due its special formulation it doesn't produce corrosion on ferrous metals.

## Application

UNIRRES NC is applied to obtain a suitable adherence between supports mainly metallic, wooden surfaces, paints and cement-based mortars, lime or gypsum.

## Surface preparation

The surface where the product is applied must be cleaned, free of greases, without rust and dry.

## Modes of application

UNIRRES NC is ready to use and no requires dilution.  
-The product must be homogenized before applying.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: desarrollo@teais.es

síguenos en:



- Spread a thin coat of the product on the surface by a brush or paint-brush.
- The initial applied product is white and becomes translucent when it is ready to mix it with mortar (mortar must be applied while the product is sticky).
- The temperature of application must be from 5 to 40°C.

## Clean up

With plenty clean water.

## Data sheet

Aspect Liquid

Colour/s White

Density 1,02 kg/l

Solid content

Adherence

Adherence

## Performance

From 4 to 5 sqm per litre

## Storage

1 year in their original package. Tightly closed without exposing it to extreme temperatures, protected from the weather and in dry and open-air places.

## Security

## Supplementary information:



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: desarrollo@teais.es

síguenos en:



EUH208: EUH208:Contains . May produce an allergic reaction.

EUH210: EUH210:Safety data sheet available on request.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

☎ Telf.: 981 602 111

📠 Fax.: 981 601 508

✉ Email.: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

