

MICROEXPAN, EXPANSIVE AND PLASTICIZER ADDITIVE FOR GROUTS AND MORTARS



Description

Expansive and plasticizer additive for concrete groutings and for improving mortars. It provides high fluency groutings and a low relationship between water/cement which improves the setting. In case of using mortar it improves the workability and reduces its plastic contraction.

Application

Microexpan can be used in the filling of foundations, groutings, non retraction fillings, etc.

Surface preparation

The application surfaces must be clean, healthy, slightly moistened.

Modes of application

Add the required amount of water to the mixing container or concrete mixer. Then slowly add cement, sand and MICROEXPAN.

Slowly mix during 5 minutes until finally obtaining a uniform and fluid mix.

- Apply the mortar within 20 minutes after mixing.
- The mortars should undergo proper curing so that they may be protected against premature drying, by

spraying them.

Clean up

With plenty of water, while the material is not hardened.

Data sheet

Aspect Greyish powder.

Density 1.167 kg/l

Performance

275 grs per 75 kg of cement.

Storage

1 year in original packaging protected from weather, in a dry place.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

