



Descripción

Mineral fibre fabric. Useful as reinforcement framework in different applications. It must be fixed in the centre of the product to be reinforced. In cracks and fissures, it is advisable to make a double reinforcement, as well as in dintel and jambs.

Aplication

It is used as reinforcement in mortars, paints, cracks and fissures.

Surface preparation

Not applicable.

Modes of application

Place in the centre of the product to be reinforced (plastic mortar, plaster, etc). The fabric is fixed into place using a serrated trowel, overlapping one fibre fabric with another until reaching 5 cm approximately. In cracks and fissures, it is recommended to establish double reinforcement, as well as in dintel and jambs.

Clean up

Not applicable.

Data sheet

Colour/swhite

WeightWeight: 109 g/m²

Mechanical Resistance: 200 daN/5 cm

CompositionFiberglass mesh

Performance

1.05 m² per sqm.

Storage

It is recommended to store this product in its original well packed rolls, protected from bleakness, with no exposure to extreme temperatures. No time limit for storage.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email.: desarrollo@teais.es

síguenos en:

