



DESPOL, POWDER PRODUCT USED AS RELEASING AGENT



Descripción

Releasing agent for plastic moulds used in manufacturing stamped concrete. It avoids the risk of breaking the pieces upon turning them out. It is sprinkled on the fresh concrete where the mould will be placed before turning out. It reduces the deterioration of the mouldings, is non-toxic and does not stain concrete.

Aplication

It is used as releasing agent in plastic moulds, avoiding the risk of breaking complex pieces upon turning them out.

Surface preparation

The product is applied onto the surface of fresh concrete mix until it fully covers it.

Modes of application

Spread the powder onto the surface of fresh concrete by applying the product uniformly.

Place the mould onto the surface on which DESPOL is evenly spread.

Once the piece hardens, remove the mould and clean or wash away the wastes.

Clean up



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



Clean using large amounts of water.

Data sheet

Powder density 0.400 ± 0.05 g/cc.

Colour/sgrey, other by order

Performance

5 m² per kg.

Storage

It is recommended to store this product for 1 year in tightly closed original packages.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email.: desarrollo@teais.es

síguenos en:

