



DEAIS MH, Special release agent for moulds made of wood and metal.



Descripción

Special release agent for moulds made of wood and metal. It is used in moulds for work and prefabs. It doesn't produce spots on concretes both normal and white and allows to obtain surfaces with excellent quality and texture. It can be used on concretes placed by traditional methods, vibrated concretes, self-compacting, etc

Aplication

It is used in all types of moulds made of wood or metal both in work and prefab industry. It can be used on concretes placed by traditional methods as vibrated, self-compacting, etc.

Surface preparation

The surface of the moulds must be cleaned, free of dust, particles, wastes of mortars or concretes and dry.

Modes of application

Shake strongly the content of the package before using.

- Apply preferably as the product is provided.
- Soluble in gas oil and other hydrocarbons.
- The application must be done with brush, roller, spray can before placing the metallic armour.
- The concretes which going to be painted on or cladding with mortars must be washed with plenty of water



and brushed with brushes to remove wastes of release-agents.

Clean up

The tools used can be cleaned with cleaning solvent

Data sheet

Density 0,85 kg/l

Aspect Oily liquid

Colour/s Amber translucent

Performance

5 to 10 sqm/l not diluted, diluted 15 to 30 sqm/l

Storage

1 year in their original packages, protected from the weather and stored in cool and dry places.

Security



Indications of danger:

H226: H226: Flammable liquid and vapour.

H304: H304: May be fatal if swallowed and enters airways.

H317: H317: May cause an allergic skin reaction.

H336: H336: May cause drowsiness or dizziness.

H412: H412: Harmful to aquatic life with long lasting effects.

Prudence advice:

P210: P210:Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: P280:Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: P301+P310:IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P302+P352: P302+P352:IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353: P303+P361+P353:IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: P304+P340:IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P370+P378: P370+P378:In case of fire: Use ABC powder extinguisher to extinguish.

P501: P501:Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH066: EUH066:Repeated exposure may cause skin dryness or cracking.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

