



ROCAMOL LISO, CRUSHED ROCK WITH SMOOTH FINISHING FOR REFURBISHMENT OF NATURAL STONE.



Descripción

ROCAMOL LISO is product based on crushed rock, cement, lime, additives and dyes that is used for renderings imitating natural stone of granite type and also for imitating stone in refurbishment and construction.

COLOURCHART REFERENCES:10; 20; 30; 40.

Sacks of 25 kgs.

Aplicación

ROCAMOL LISO is used to imitate existing natural stone in colour and texture in constructions where refurbishment are required and also to do renderings alone or mixed with stone.

Surface preparation

The support must be clean, firm, resistant, free of greases, oils or polluting agents and must be slightly wet.

Modes of application

ROCAMOL LISO is mixed with water in proportion of 180 cc of water per kg of product (form 4 to 5 lts per bag of ROCAMOL LISO).

- The admixture must be done manually or low-revolution electric mixer (300-400 rpm) y helicoidal pallet.
- The material must be spread by trowel or pallet according with areas to render on. Then the surface must be



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

Tel.: 981 602 111

Fax.: 981 601 508

Email: desarrollo@teais.es

síguenos en:



finished as a smoothed surface.

- The maximum thickness of the application must not be higher than 20 mm.
- Once ROCAMOL is applied, avoid the direct sunlight, rain, snow or freezes. It shouldn't be applied with temperatures below of 5°C or over 30°C.

Clean up

Tools must be cleaned with water while the product is wet. After only can be removed by mechanical means.

Data sheet

Water absorption $18 \pm 2\%$

Powder density $1,400 \pm 0,05$ g/cc

Mass of density $1,850 \pm 0,05$ g/cc

Capillarity < 0,50% 60 minutes

Water retention > 97%

Compressive resistance > 50 kg/cm²

Flexural strength resistance > 10 kg/cm²

Adherence > 5 kg/cm²

Colour/s According colour chart

Performance

From 15 to 18 kg per sqm 10 of thickness

Storage

2 years in their original packages tightly closed, protected from the weather and stored in dry place.

Security



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

☎ Telf.: 981 602 111

📠 Fax.: 981 601 508

✉ Email: desarrollo@teais.es

síguenos en:



Indications of danger:

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H318: Causes serious eye damage.

H335: May cause respiratory irritation.

Prudence advice:

P271: Use only outdoors or in a well-ventilated area.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P310: Immediately call a POISON CENTER or doctor/physician.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

