



REMOZADOR DE ACERAS, PRODUCT TO IMPROVE THE APPEARANCE AND DURABILITY OF SIDEWALKS MADE OF CEMENT TILES.



Descripción

Powder product that is mixed with water in grouting consistence and is applied over trowelled mortar or concrete sidewalks or cement slabs.

For flooring aesthetic renewal, it pluggs small pores in flooring as well as areas where the decreasing of water absorption is required. It is very suitable for slabs in landscaped areas. Grey colour.

Application

Renovation agent for sidewalks that is applied to improve the appearance of the floorings made of cement or concrete mortar or cement tiles.

Surface preparation

The surface of application must be clean and wet in the moment of application. Repairs that require certain quantities of material must be done previously taking into account that the renovation agent is a thin layer.

Modes of application

It must be blended with water until achieve a grouting consistency.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



- Let it stand from 3 to 5 minutes before applying.
- Wet the ready support slightly.

Clean up

Used tools must be cleaned with water while the product is wet. After it hardens only can be removed by mechanical means.

Data sheet

Adherence > 0,5 N/mm²

Water absorption 25 + - 5%

Powder density 1,15 gr/cc

Curing density 1,72 gr/cc

Water retention > 98%

Capillarity < 1,8 % 60 minutes

Compressive resistance > 280 kg/cm²

Flexural strength resistance > 90 kg/cm²

Temperature of work from 5°C to 30°C

Open time > 20 minutes at 20°C

Colour/s grey

Performance

1 kg per sqm approx.

Storage

Two years in their original packages stored in dry place.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

