



TEAIS APAREJO MICROCEMENTO, Special plaster used to regularize a tile floor before applying TEAIS MICROCEMENTO.



Descripción

TEAIS APAREJO MICROCEMENTO is a special mortar, suitable for the ceramics supports regularization and finishing with TEAIS MICROCEMENTO.

Aplication

It is applied to regularize ceramic tiled surfaces, chipboard, and other supports where regularization is needed before applying TEAIS MICROCEMENTO.

Surface preparation

The support must be clean, free of grease or oil, firm, without loose parts and dry.

Modes of application

- Mix manually or mechanically the liquid with the powder component until a thixotropic paste is obtained.
- Mix manually or by using a low speed mixer(300 to 500 r.p.m.).
- Let stand 2-5 minutes before using.
- Apply a first thin coat with a stainless steel to cover only the joints; the surface should be clean and dry.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



- Let dry and apply a coat of our primer IMPRIDUR.
- Let it dry and apply another coat covering all the surface with TEAIS APAREJO MICROCEMENTO.
- Allow to dry before applying TEAIS MICROCEMENTO

Clean up

The tools are cleaned with water while the material is fresh.

Data sheet

Adherence > 0,5 N/mm²

Mass of density 1,76 kg/lt

Mix proportion 3 part of powder for 1 part of liquid

Open time > 20 minuts at 20°C

Performance

1,5 to 2 kg/sqm

Storage

Two years in their original containers tightly closed. Protected from weather and stored in a cool and dry place.

