



Descripción

Asphaltic and manageable emulsion under ambient temperature for primer and waterproofing every kind of surface. Black colour.

Aplication

It's used to printing and waterproofing surfaces to be treated with bituminous products, protection and waterproofing foundations, basements, retaining walls, etc.

Surface preparation

The application surface must be clean, without dust, greases, paint wastes. The area should not be excessively smooth, for adhesion reasons.

Modes of application

- Homogenize well the contents of the packaging
- Apply with brush or roller, never under adverse weather conditions such as rain or temperatures below 5 ° C.
 - Each coat must be dry before applying the next one.
 - If it is used as a primer it may be diluted with water at a ratio of 10 to 20%.
 - If it is used as a protection for foundations or walls, a first coat can be apply diluted and then applied two or three layers without any dilution.

- Avoid getting wet during the first 24 hours. Exposure to strong sunlight should be avoided after application

Clean up

Clean using our solvent DISOLUAIS while the product is fresh.

Data sheet

Colour/sblack

Density 1.00 Kg/L (\pm) 0.05 g/cm³ at 20°C.

Solid content in volume 61.1 (\pm) 0.05 %.

Composition Bitumen-rubber emulsion.

Temperature of work 5 to 30 °c

Performance

1.5 kg per m² in two 500 micron coatings.

Storage

It is recommended to store this product for 1 years in tightly closed original packages in a cool dry place at temperatures above 5°C.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email.: desarrollo@teais.es

síguenos en:

