



DURIMPRES, COLOURING POWDER AND HARDENER USED FOR STAMP CONCRETE PAVEMENTS



Descripción

Colouring powder and surface hardener for printed concrete paving that is applied onto the fresh concrete mix. It hardens concrete and colour it at the same time.

Colours: grey. Other colours price according with colour and amount of order. Colour chart.

Aplicación

It is used for hardening and colouring stamped concrete.

Surface preparation

The product is applied onto the fresh concrete until fully covering the support. Leave to act during some minutes.

Modes of application

The powder product is spread onto the fresh concrete until it is uniformly applied. Leave to act for a couple of minutes.

Apply the powder releasing agent DESPOL.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



Place the mould on the surface of the fresh concrete mix.
Once the concrete hardens, remove the mould.

Clean up

When using a tool during the application, clean using water and leave to dry before using again.

Data sheet

Density 1.25 kg/L \pm 0.05 g/cc

Colour/s Wide range of colours.

Composition quartz aggregates, special cements, inorganic pigments, additives.

Average thickness 2 to 2.5 mm for consumption of 4 kg / m² aprox

% Solid content in weight

Temperature of work 5 to 30°C

Performance

3 to 5 kg per m²

Storage

It is recommended to store this product for 2 years in tightly closed original packages.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

