



## Descripción

Transparent liquid based on parafins emulsion for working as protection membrane of cement curing on concretes and wet mortars.

## Aplication

Its application to newly laid concrete floors, forms a film that prevents premature loss of water. Without altering the setting time. As protector for curing fresh cement and mortar. Improves physical resistances.

## Surface preparation

Not applicable.

## Modes of application

Mix the content of the package before so as to make it uniform.

- Apply directly onto the mortar or concrete with a spray.
- It is recommended to apply in two continuous coatings.

Application is only possible once it is observed that the surfaces of application become matt.

- Surfaces to be finished with mortar or paint must not be treated with LACURIS A or proceed to sanding the surface to ensure proper adhesion.

## Clean up

Clean tools and spray equipment with Disolvente de Limpieza immediately after using.

## Data sheet

Colour/scloudy white

Density 0.98 gr/ml. At 20 ° C

## Performance

8 sqm per l (min).

## Storage

2 years in their original packagings, properly closed and at moderated temperatures, stored in a dry and cool place.

## Security

## Supplementary information:

EUH210: Safety data sheet available on request.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: desarrollo@teais.es

síguenos en:

