

TEAIS PAVIFORTE, Hardening liquid treatment and consolidating.



Descripción

Liquid treatment with consolidant effect to apply on concrete pavements. It hardens deeply keeping the aesthetic appearance. Suitable for industrial pavements, cementitious pavements. Improves the resistance against abrassion and has anti-dust effect.

Aplication

TEAIS PAVIFORTE is used for surface consolidation of concrete and polished-concrete industrial pavements. Warehouses, shopping centers, parkings, etc. Improves the resistance to abrassion on cementitious pavements. Improves the resistance to

Surface preparation

The support must be clean, free of dust, particles. The support must be consisting. It shouldn't have greases and oils. The surface must be dry, without humidity and water.

Modes of application

Teais Paviforte can be applied after 2 or 3 days of concrete pouring or joint cutting.

- In the case of already cured joints it is applied directly on the clean and dry support and free of treatments or paints or any other substances which may hinder the penetration fo consolidating treatment.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
 15143 Arteixo, A Coruña
 Telf.: 981 602 111
 Fax.: 981 601 508
 Email.: desarrollo@teais.es



- It can be applied by pouring directly on the floor homegeneously. Is neccessary to avoid dry and wet zones at the same time. The liquid must be onto the support betwenn 20 and 30 minutes.

- Once the time has past the exceed of liquid must be removed drying and polishing the treated surface.
- Finishing the spreading and drying operation is suitable to don't walk at least for a couple of days on it.
- It is recommended to do a previos test in order to check the consumption of the product.

Clean up

Tools must be cleaned while the material is fresh.

Data sheet

Colour/sTraslucent liquid Density1,12 kg/lt PH11 Temperature of workfrom 5°C to 30°C

Performance

200 to 400 grs/sqm according support absorption

Storage

One year in their original packages protected from the weather and stored in cool and dry places.

Security



Indications of danger:

H315: Causes skin irritation.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
 15143 Arteixo, A Coruña
 Telf.: 981 602 111
 Fax.: 981 601 508
 Email.: desarrollo@teais.es



Prudence advice:

P264: Wash ? thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P337+P313: If eye irritation persists: Get medical advice/attention.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

- Telf.: 981 602 111
 Fax.: 981 601 508
- ✓ Email.: desarrollo@teais.es

