



# IMPRIMAIS MR, FAST-DRY ANTIRUST PRIMER.



## Descripción

Fast dry time antirust primer for protecting metallic surfaces.  
Solvent: DISOLUAIS. Colours: Red, Grey and Black.

## Aplicación

As a primer and protection of car bodies, truck cabins, vans, bikes, metallic structures, etc

## Surface preparation

The surface must be clean, free of dust, greases, oils and other polluting agents that avoids a good adherence on the supports and a perfect finish.

## Modes of application

Shake well the content of the package before using.

Once the surface is cleaning up, dry and free of rust, prime with diluted layer from 10% to 30% with DISOLUAIS by spray gun.

Allow 30 minutes (minimum) and apply a second layer by the same way.

- Allow it dry at least 8 hours at 20°C for applying the finishing.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: desarrollo@teais.es

síguenos en:



Protect with a finish based on synthetic enamels ESMAIS AND ESMAR.

## Clean up

With grease- based solvent DISOLUAIS.

## Data sheet

Density 1,27 Kg./Lt. +- 0,05

Solid content in volume  $47 \pm 1 \%$

Combustion point up to 25 °C

Dry upon touching < 2 Hours

Dry for repainting 4 Hours /20°C/65% (with enamels).

Dry film thickness 25 microns minimum

Temperature of work from 5°C to 30°C

Colour/s Malaga Red

## Performance

5 sqm per litre.

## Storage

2 years in their original packages and tightly closed, stored in a dry and cool place and protected from the weather.

## Security



## Indications of danger:



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: desarrollo@teais.es

síguenos en:



H226: Flammable liquid and vapour.  
H304: May be fatal if swallowed and enters airways.  
H312: Harmful in contact with skin.  
H315: Causes skin irritation.  
H317: May cause an allergic skin reaction.  
H319: Causes serious eye irritation.  
H340: May cause genetic defects .  
H350: May cause cancer .  
H372: Causes damage to organs through prolonged or repeated exposure .  
H373: May cause damage to organs through prolonged or repeated exposure .  
H411: Toxic to aquatic life with long lasting effects.  
H200: Unstable explosives.

## Prudence advice:

---

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.  
P280: Wear protective gloves/protective clothing/eye protection/face protection.  
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P308+P313: IF exposed or concerned: Get medical advice/attention.  
P370+P378: In case of fire: Use ? for extinction.  
P501: Dispose of contents/container in accordance with local/regional/national/international regulation

## Supplementary information:

---

EUH066: Repeated exposure may cause skin dryness or cracking.  
EUH208: Contains . May produce an allergic reaction.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email: desarrollo@teais.es

síguenos en:

