



Descripción

Primer and antioxidant paint for protecting metallic surfaces applicable by brush or spray gun. Free of Zinc Chromate. Grey colour. Solvent: DISOLUAIS.

Aplication

As primer and paint at the same time (only in indoors), on metallic surfaces made of iron or steel. On surfaces which are not made of iron or steel is necessary to do a previous treatment with IMPRIGALVI. In outdoors only is suitable to use as a primer on metallic surfaces made of iron or steel for subsequent finishing with a synthetic enamel such as ESMAIS OR ESMAR.

Surface preparation

The surface must be clean, free of dust, oils and other polluting agents which decreases the adherence on the supports and provides a perfect finish.

Modes of application

Shake and stir well the containt of the package before using.

Apply two layers by brust using DISOLUAIS as solvent in the minimum quantity required for a correct

application.

Allow at least 6 hours between layers.

In indoors, its application turns in a antirust finishing.

In outdoors, protect with two layers of synthetic enamel such as ESMAIS, ESMAR the only suitable products.

Clean up

With Teais solvent DISOLUAIS while the product is wet.

Data sheet

Density 1,45 Kg./Lt. +- 0,05 at 20°C.

Solid content in volume 56 ± 1 %

Temperature of work from 5°C to 30°C

Dry upon touching < 3 hours at 20°C

Colour/s grey

Dry for repainting 6 hours at 20°C /65%

Dry film thickness 60 microns

Aspect Matt

Performance

7 sqm per litre.

Storage

2 years in their original packages, tightly closed, stored in dry and cool place and protected from the weather.

Security



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

☎ Telf.: 981 602 111

📠 Fax.: 981 601 508

✉ Email: desarrollo@teais.es

síguenos en:



Indications of danger:

H226: Flammable liquid and vapour.

H315: Causes skin irritation.

H332: Harmful if inhaled.

H340: May cause genetic defects .

H350: May cause cancer .

H373: May cause damage to organs through prolonged or repeated exposure .

H411: Toxic to aquatic life with long lasting effects.

Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH208: EUH208:Contains . May produce an allergic reaction.

