



Descripción

Application

Modes of application

Data sheet

Density

Viscosity

Thin layer

Dry upon touching

Dry for repainting

Temperature of work

Storage

Security



Indications of danger:

- H225: Highly flammable liquid and vapour.
- H304: May be fatal if swallowed and enters airways.
- H312: Harmful in contact with skin.
- H332: Harmful if inhaled.
- H315: Causes skin irritation.
- H319: Causes serious eye irritation.
- H335: May cause respiratory irritation.
- H350: May cause cancer .
- H360: H360Df:May damage fertility or the unborn child .
- H373: May cause damage to organs through prolonged or repeated exposure .
- H373: May cause damage to organs through prolonged or repeated exposure .
- H400: Very toxic to aquatic life.
- H410: Very toxic to aquatic life with long lasting effects.

Prudence advice:

- P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.
- P280: Wear protective gloves/protective clothing/eye protection/face protection.
- P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
- P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.





P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH205: Contains epoxy constituents. May produce an allergic reaction.

EUH208: Contains . May produce an allergic reaction.



 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
 Telf.: 981 602 111
 Fax.: 981 601 508
 Email.: desarrollo@teais.es

síguenos en:

