



TEAIS PROTEMAX, PROTECTOR AND SEALER AGAINST STAIN



Descripción

Liquid product of high fluidity and great capacity of penetration, based on synthetic resins monocomponentes that is applied on mineral surfaces porous (of fine or medium pore). As a protector and sealant of stone pavements, polished concrete, porous ceramic. As a sealer on countertops in kitchens or bathrooms. Avoid watermarks on elastomers type Lastois Techumbres or Lastois Cubiertas. It also acts as a protector on vinyl labels. In vertical walls covered with stone, porous ceramic, or mineral coatings in general.

Aplication

As a protector and sealant of stone pavements, polished concrete, porous ceramic. As a sealer on countertops in kitchens or bathrooms. Avoid watermarks on elastomers type Lastois Techumbres or Lastois Cubiertas. In vertical walls covered with stone, porous ceramic, or mineral coatings in general.

Surface preparation

The support must be clean, free of dust or substances that impair adhesion. In the case of porous supports, it is necessary to wet beforehand to cut the absorption, and wait until the surface begins to dry for the application.

Modes of application

- Thoroughly homogenize the product by stirring it before application.
- Moisten the support in a homogeneous way and when the humidity is disappearing, made the application.



Do not place on dry supports. The wetting of the support can be done by wetting with hose or by spraying generously and homogeneously.

- Apply preferably with a short hair roller, avoiding overlapping of hands because because it can be noted the effect of overlap..
- If a second layer is required, wait at least one hour after applying the second one.
- It is necessary to make tests of the application of the protection to see if the aesthetic aspect is the one sought.
- In the application on stone is necessary to make a test to verify that the aesthetic aspect is the one desired.

Clean up

The application tools must be cleaned with Disoluais N, in fresh.

Data sheet

Aspect Translucent slightly cloudy

Density 0,84 kg/lt

Odour characteristic

Dry upon touching 30 minutes at 20 ° C and 65% RH

Temperature of work 8 at 25°C

Performance

5 to 6 sqm/lt

Storage

Two years in its original packaging protected from the elements, stored in a cool and dry place.

Security



Indications of danger:

H225: H225:Highly flammable liquid and vapour.

H319: H319:Causes serious eye irritation.

H336: H336:May cause drowsiness or dizziness.

Prudence advice:

P210: P210:Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: P280:Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: P303+P361+P353:IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: P304+P340:IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: P305+P351+P338:IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P370+P378: P370+P378:In case of fire: Use ABC powder extinguisher to extinguish.

P403+P233: P403+P233:Store in a well-ventilated place. Keep container tightly closed.

P501: P501:Dispose of contents/container in accordance with local/regional/national/international regulation

