

DEPIS ANTIMOHO LISA, INDOOR AND OUTDOOR PLASTIC PAINT



Descripción

Plastic paint soluble on water for using only in interiors to protect against mold and moisture. White matt colour and smooth finish. Basic colours.

Aplication

It is used on walls and ceilings in interiors. Onto renders or cement based mortars, plaster, gypsum, perlite plaster, fibrocement, concrete slips, etc.

Surface preparation

The background of application must be clean, free of grease, oil, dust, lime based paints, by being perfectly compact and dry.

Modes of application

Use IMPRIMAIS SUPER or IMPRIMAIS M.U. primer (according to the type of support).

Apply with a paint brush, roller or sprayer gun.

Apply the first coating using DEPIS LISA ANTIMOHO by





Email.: desarrollo@teais.es

diluting 10 to 20% in water(according to primer).

Once the first coating is dry, apply the second one undiluted.

A satin finish is achieved with ACRILAIS TRANSLÚCIDA ANTIVERDIN, diluted to 30%...

- -Resistant to alkaly, wear and interior moisture.
- Soluble in water, colour-changeable and look smooth- matt.

Clean up

With plenty of water

Data sheet

Density1,64 Kg./Liter ± 20°C

Viscosity37.500 ± 7.500 at 20°C

Dry film thickness45 microns.

Dry upon touching1 Hour /20°C/65% de R.H

Dry for repainting8 Hours /20°C/65% de R.H.

Totally dry24 Hours /20°C/65% de R.H.

Colour/swhite and other colours under order

Performance

3 sqm per kg.

Storage

It is recommended to store this product for 2 years at most in tightly closed original packages in a cool dry place.

Security





Indications of danger:

H412: Harmful to aquatic life with long lasting effects.

Prudence advice:

P273: Avoid release to the environment.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH208: Contains . May produce an allergic reaction.



