



LUMINOIS FLUORESCENTES, SYNTHETIC PAINT THAT REACTS WITH THE LIGHT (L-20)



Descripción

Aplicación

In the signage of garages, underground car parks, posters indicating warnings, dangers, etc.

Surface preparation

It must be well cleaned, degreased and perfectly dry. Indispensable to treat your background with white color.

Modes of application

Homogenize the contents of the container before proceeding with the application.

-Apply a white background, depending on the type of surface will apply the type of background, either synthetic for metals or wood or plastic paint for walls of mortar or concrete.

-Apply by brush, roller or gun.



Clean up

With our solvent DISOLUAIS

Data sheet

Density $0,87 \pm 0,05$ kg./Liter at 20°C

Viscosity 80 ± 30 seconds. Ford Cup: 4 mm. at 20 ° C

Dry for repainting 4 Hours / 20°C

Colour/sred and green fluorescent, others on request.

Dry film thickness 40 microns.

Aspectmate.

Temperature of work 5 ° C to 30 ° C

Performance

5 m² per l.

Storage

1 year, in their original and tightly closed bottles, stored in a dry and cool place totally protected from the elements.

Security



Indications of danger:

H225: Highly flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H350: May cause cancer .

H362: May cause harm to breast-fed children.

H411: Toxic to aquatic life with long lasting effects.

Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.

