

Descripción



Application

Modes of application

Data sheet

Density

Viscosity

Hard dry

Thin layer

Temperature of work

Storage

Security



Indications of danger:

- H225: Highly flammable liquid and vapour.
H304: May be fatal if swallowed and enters airways.
H315: Causes skin irritation.
H319: Causes serious eye irritation.
H332: Harmful if inhaled.
H335: May cause respiratory irritation.
H351: Suspected of causing cancer .
H362: May cause harm to breast-fed children.
H373: May cause damage to organs through prolonged or repeated exposure .
H411: Toxic to aquatic life with long lasting effects.

Prudence advice:

- P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313: IF exposed or concerned: Get medical advice/attention.
P370+P378: In case of fire: Use ? for extinction.
P501: Dispose of contents/container in accordance with local/regional/national/international regulation

Supplementary information:

EUH066: Repeated exposure may cause skin dryness or cracking.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email.: desarrollo@teais.es

síguenos en:

