



PINDAIS LISA, PLASTIC PAINT FOR INDOORS AND OUTDOORS



Descripción

Plastic paint to water indoor and outdoor use, designed to decorate and protect, smooth finish. Basic colors.

Aplication

In facades, patios, pillars, party walls, balconies, towers, domes, etc. It is generally used in ceilings and walls in indoors and outdoors.

Surface preparation

Must be clean, without greases, dust, lime paints, tempera, oil paints and appearing compact and dry.

Modes of application

Mix the contents of the container well.

Apply with a paint brush, roller or gun.

The first coating is applied by diluting 10 to 20% in water.


The second coating is applied without diluting.

For a satin finish achieved by using ACRILAIS TRANSLUCIDA (ANTIVERDIN)



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:



in exteriors), by diluting 30% in water.

Primers that can be used: IMPRIMAIS o IMPRIMAIS M.U. (depending on the type of support).

Clean up

With plentiful clean water, while the product is fresh.

Data sheet

Density 1,6 Kg./Liter \pm 0,05 a 20°C

Viscosity 1,6 Kg./Liter \pm 0,05 a 20°C

Totally dry 24 Hours/50 microns/20°C/65% de H.R

Dry for repainting 8 Hours/50 microns/20°C/65% de H.R

Aspect smooth and mat

Colour/white and other regarding color chart

Performance

3 sqm per kg.

Storage

2 years, in their original packagings and properly closed, stored in a cool and dry place and protected from the weather.

Security

Supplementary information:



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
Telf.: 981 602 111
Fax.: 981 601 508
Email: desarrollo@teis.es

síguenos en:



EUH208: Contains . May produce an allergic reaction.

EUH210: Safety data sheet available on request.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email: desarrollo@teais.es

síguenos en:

