

PINTIS LISA, WASHABLE PLASTIC PAINT FOR INDOORS - OUTDOORS



Descripción

Washable plastic paint for interior and exterior. On surfaces, plaster, cement, cement-based plasters, etc.. basic colors

Aplication

On ceilings and walls. On plasters and cement-based plastes, gypsum, asbestos cement, etc.

Surface preparation

Must be clean, without greases, dust, lime paint, tempera, oil and appearing compact and dry.

Modes of application

Apply using a paint brush, roller or gun.

The first coating is applied by diluting 10 to 20% in water.

The second coating is applied without diluting.

A satin finish is achieved using ACRILAIS TRASLUCIDO diluted to 30%.

IMPRIMAIS SUPER, IMPRIMAIS M.U. or IMPRIMAIS NORMAL primer is used(depending on the type of support).





Email.: desarrollo@teais.es

Clean up

With plentiful clean water.

Data sheet

Density1.6 Kg/Liter ± 0,05

Viscosity42.500 ± 7.500 mPa.s

Dry for repainting8 Hours/50 micron/20°C/65% of R.H.

Aspectsmooth and matt.

Colour/ssnow white

Temperature of work5° to 30°C

Performance

3 sqm per kg

Storage

2 años, en sus botes originales y bien cerrados protegidos de la intemperie y almacenados en lugar fresco y seco.

Security

Supplementary information:

EUH208: EUH208: Contains mixture of: 5-chloro-2-methyl-4-isothiazolin-3-one [EC no. 247-500-7] and 2-methyl-2H -isothiazol-3-one [EC no. 220-239-6] (3:1). May produce an allergic reaction.

EUH210: EUH210: Safety data sheet available on request.





Email.: desarrollo@teais.es