

## Descripción



## Application

### Modes of application

### Data sheet

- Dry film thickness
- Density
- Dry upon touching
- Totally dry
- Dry for repainting
- Resistance to heat
- Solid content in volume
- Aspect

Colour/s

Temperature of work

Temperature of service

## Storage

## Security



### Indications of danger:

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H332: Harmful if inhaled.

H336: May cause drowsiness or dizziness.

H372: Causes damage to organs through prolonged or repeated exposure .

H411: Toxic to aquatic life with long lasting effects.

### Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P370+P378: In case of fire: Use ? for extinction.

P403+P233: Store in a well-ventilated place. Keep container tightly closed.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

## **Supplementary information:**

---

EUH066: Repeated exposure may cause skin dryness or cracking.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
☎ Telf.: 981 602 111  
📠 Fax.: 981 601 508  
✉ Email.: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

