



## Descripción

Paint based on caoutchouc chloride resistant to moisture. Specially designed for pools, water-tanks, tanks both fresh and salt water, over cement-based mortar or similar. Colours: pale blue and white.

## Application

### Modes of application

### Data sheet

Density

Viscosity

Dry upon touching

Dry for repainting

Colour/s

### Performance

From 2 to 3 sqm per litre

## Storage

## Security



### Indications of danger:

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H319: Causes serious eye irritation.

H332: Harmful if inhaled.

H335: May cause respiratory irritation.

H362: May cause harm to breast-fed children.

H373: May cause damage to organs through prolonged or repeated exposure .

H411: Toxic to aquatic life with long lasting effects.

### Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

## Supplementary information:

---

EUH205: Contains epoxy constituents. May produce an allergic reaction.

EUH208: Contains . May produce an allergic reaction.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

☎ Telf.: 981 602 111

📠 Fax.: 981 601 508

✉ Email: [desarrollo@teais.es](mailto:desarrollo@teais.es)

síguenos en:

