

## Descripción



## Application

### Modes of application

## Data sheet

Density

Colour/s

Dry upon touching

Solid content in volume

Dry for repainting

Aspect

## Storage

# Security



## Indications of danger:

H226: H226:Flammable liquid and vapour.

H315: H315:Causes skin irritation.

H319: H319:Causes serious eye irritation.

H332: H332:Harmful if inhaled.

H334: H334:May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: H335:May cause respiratory irritation.

H373: H373:May cause damage to organs through prolonged or repeated exposure.

## Prudence advice:

P210: P210:Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.

P280: P280:Wear protective gloves/protective clothing/eye protection/face protection.

P304+P340: P304+P340:IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P312: P312:Call a POISON CENTER or doctor/physician if you feel unwell.

P314: P314:Get medical advice/attention if you feel unwell.

P342+P311: P342+P311:If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

P370+P378: P370+P378:In case of fire: Use ABC powder extinguisher to extinguish.

## Supplementary information:

EUH204: EUH204:Contains isocyanates. May produce an allergic reaction.