



Descripción

LASTOIS SPT is a traslucent polymer sealant with nanoparticles of silica. By its characteristics it can be applied on stone sealing, wood works, on mortars, concretes, wood, etc. Is high resistant to UV radiation and weather. Once it is cross-linked the dust doesn't stick on it. It can't be used as an adhesive.

Aplication

LASTOIS SPT is used for sealing several types of surfaces mainly made of stone, works of wood, fissures, joints, in refurbishment and construction works. It can't be used as an adhesive.

Surface preparation

The support of application must be clean and dry, free of dust and loose particles.

Modes of application

It is applied by silicon gun, spatula, trowel, etc.
- The product has doughy consistence.

Clean up

The tools must be cleaned with plenty of water while the material is wet.

Data sheet

Colour/sTraslucent

Density1,3 kg/lt

Performance

1,3 kg/lt

Storage

One year in their original packages protected from the weather and stored in a cool and dry place.

Security



Indications of danger:

H312: Harmful in contact with skin.

H317: May cause an allergic skin reaction.

Prudence advice:

P261: Avoid breathing dust/fume/gas/mist/vapours/spray.

P272: Contaminated work clothing should not be allowed out of the workplace.

P273: Avoid release to the environment.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P332+P313: If skin irritation occurs: Get medical advice/attention.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón
15143 Arteixo, A Coruña
☎ Telf.: 981 602 111
📠 Fax.: 981 601 508
✉ Email.: desarrollo@teais.es

síguenos en:

