



## Descripción

FIJOPI is a superficial hardener of sandstone. Produces the superficial hardening of the structure where is applied on.

## Application

It is applied on all types of sandstone and several supports that can be superficially disaggregated such as coverings, mud walls, lime-mortar joints, etc.

## Surface preparation

The surface must be clean, dry, free of greases, oils, free of dust and loose particles.

## Modes of application

Apply only one layer, quiet spreading and preferably by sprayer gun.  
- FIJOPI is just a superficial hardener. When consolidating stone works are required a previous application of ENDUPIS must be done. ENDUPIS is a geological hardener based on ethylsilicate that provides hardening in the medium and long term and subsequently finish with a layer of FIJOPI if the surface requires an immediate superficial fixing.

## Clean up

With solvent DISOLUAIS.

# Data sheet

Density 0,8 kg/Lt  $\pm$  0,05 at 20 °C.

Viscosity 16 seg. A 20 °C.

## Storage

2 years in their original packages tightly closed.

## Security



## Indications of danger:

H226: Flammable liquid and vapour.

H304: May be fatal if swallowed and enters airways.

H315: Causes skin irritation.

H317: May cause an allergic skin reaction.

H336: May cause drowsiness or dizziness.

H362: May cause harm to breast-fed children.

H372: Causes damage to organs through prolonged or repeated exposure.

H411: Toxic to aquatic life with long lasting effects.

## Prudence advice:

P210: Keep away from heat/sparks/open flames/hot surfaces. ? No smoking.



Avda. da Enerxía, nº 153, Pol. Ind. de Sabón  
15143 Arteixo, A Coruña  
Telf.: 981 602 111  
Fax.: 981 601 508  
Email: desarrollo@teais.es

síguenos en:



P280: Wear protective gloves/protective clothing/eye protection/face protection.

P302+P352: IF ON SKIN: Wash with plenty of soap and water.

P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

P308+P313: IF exposed or concerned: Get medical advice/attention.

P370+P378: In case of fire: Use ? for extinction.

P501: Dispose of contents/container in accordance with local/regional/national/international regulation

## Supplementary information:

---

EUH066: Repeated exposure may cause skin dryness or cracking.

EUH208: Contains . May produce an allergic reaction.



📍 Avda. da Enerxía, nº 153, Pol. Ind. de Sabón

15143 Arteixo, A Coruña

☎ Telf.: 981 602 111

📠 Fax.: 981 601 508

✉ Email: desarrollo@teais.es

síguenos en:

